



TDCORE A9 - 15.6" Widescreen Touch EPOS

Heavy-duty cast alloy baseplate, high quality components and a true flat splash-proof widescreen, all at a competitive price.

The **TDCORE A9** is a superb design that meets all the key needs of a truly great touch EPOS system. It looks good, uses high quality components and it is built for long-life with high reliability.

- Stylish super-slim wide polymer screen casing
 just 1.5cm deep at edge
- 15.6" 1366 x 768 display means 33% more content and higher resolution (than 15" 4:3)
- Quad-Core 2GHz Intel J4125 CPU can run Windows or Linux
- 4GB DDR4 RAM, 128GB SSD with 3-year warranty
- Heavy-duty cast alloy baseplate for stability, industrial touch screen (PCAP)
- Able to run Windows 8, 10, 11 or Linux
 (TDCORE version pre-installed with Win 10 IoT)



TDCORE: QUALITY EPOS EQUIPMENT AT ULTRA-COMPETITIVE PRICES

Available Options






2-line customer LCD display











TDCORE A9 - specifications and performance data

System controller and	l storage	Power supply	
Controller Board	J4125 Intel	Type - external	Inline switch mode
Processor	Quad Core Intel 2GHz	Output cable	1.5M DC cable male jack
Hard Disk	128GB SSD	Output power	DC12V/5A
RAM	4GB DDR4 RAM	Input power	100-250v / 50-60Hz
Screen		Input cable	1.5M IEC with UK 3 pin plug
LCD screen	Industrial grade 15.6" 1366 x 768	Operating Systems	
Brightness	250cd/m2 LED backlit	Win 10 IoT	Pre-installed
Splash/Dust proofing	Approx IP55	Can also run	Win 10, 11 or Linux
Aspect Ratio	16:9 Widescreen (Landscape)	Size & weight	
Touch control	PCAP	Unit Standalone	38x19x33.5cm (wxdxh) 5.4kg
Cooling		Packaged size	43x27x41cm (wxdxh) 7kg
No fan heat sink design	Noiseless	Warranty	
Inputs & Outputs on	rear bottom	Period & terms	36 months RTB
Serial external COM 1	9 pin D RS232		
USB Ports	2 x USB 3.0, 3 x USB 2.0		
LAN	1 x RJ45 female 1GBps		





Audio

Multiple Park, Finepoint Way, Kidderminster, DY11 7FF

1 x line in, 1 x line out

5VDC male in & out



01299 488031

DC Power 2.4mm jack



info@tills-direct.com

